

A



SVÍTIDLO HARRIER-LED-4950-4K DIM DALI, Interior LED luminaire, 1x LED, 42.0 W 3650 lm 86.9 lm/W, IP20

B



SVÍTIDLO GRIFON-LED-MP-3200-4K, Interior lighting, 1 x LED, 24.0 W, 2791 lm, 116.3 lm/W, IP40

C




SVÍTIDLO FOX-LED-2900-4K, Interior lighting, 1 x LED, 19W, 2312lm, 121.7 lm/W, IP40

D



SVÍTIDLO GRIFON -LED-AS-7000-4K, Interior lighting, 1 x LED, 48.0 W, 4323 lm, 90.1 lm/W, IP40

N1



SVÍTIDLO NOUZOVÉ PALAS-LED-1-M2-ST, 1h, IP65, Emergency lighting, 1x LED, 6.6 W, 241 lm (100 %)

N2



SVÍTIDLO NOUZOVÉ DIOS-COR-C2-1H, Emergency lighting, 1 x LED, 6.0 W, 481 lm, 80.2 lm/W, IP65



1 - pól. spínač 10AX, 250V AC, typ tango bílá



Střídavý spínač 10AX, 250V AC, typ tango bílá



SB..

Tlačítko spínač 10A, 250V AC, typ tango bílá



Zásuvka jednonásobná s ochranným kolíkem a clonkami 16A, 250V AC, IP 40, typ tango bílá



Zásuvka jednonásobná s ochranným kolíkem a clonkami 16A, 250V AC, IP 40, typ tango bílá s přepěťovou ochranou

SKR



Stávající datový rozvaděč

ER



Rozvaděč školního rozhlasu

M1
0,028

Elektrický ventilátor, 230V, P=0,028 kW, IP X4 s časovým nastavitelným modulem, viz dodávka zařízení VZT

ASP



Vývod pro automatický splachovač pisoáru

R 2.1



Rozvaděč OCEP EATON TYP BP-U-DWB-800/15-EIS, IP40, sest. dle výkresu EI 0.5



V uvedeném prostoru bude provedeno doplňkové ochranné pospojení



Uzemnění na strojený základový zemnič domu

POP



Pomocná ochranná připojnice