







MOVIBLOC M3 SERIES
SISTEM MANUAL-MECHANIC OPERATION
LOAD PER SHELF:100 kg
MAXIMUM LOAD OF THE CUPBOARD: 4440 kg
MAXIMUM LOAD ON CENTRAL WHEEL: 1086 kg
FORCE NEEDED TO OPERATE CUPBOARD: 4 kg
BASE LOCK
X: SIDE CLADDING

Nabízíme aktualizaci systému řízení vašeho skladu softwarem Mecalux

easywms

www.mecalux.cz/easy

User confirmed the loads imposed by the rack and their impact on the floor
User confirmed the distribution of racks in respect to the dilatation network
User confirmed the layout of racks and its compliance with the industrial safety and fire regulations
User confirmed the room measurements and the racking installation dimensions
THE DESIGN AND THE QUOTATION ARE PROVISIONAL AND THEY CAN BE MODIFIED BY MECALUX IN FUNCTION OF THE DEFINITIVE CALCULATION.



Všechny uvedené rozmiry jsou jmenovité a mohou se lišit v závislosti na typu použitých profilů a na výrobních a montážních tolerancích povolených v pøíslušných normách.

VÝKRES

VYHOT.	ZKONT.	DATUM	INDEX

MECALUX

Zákazník:

Mìsto Èeský Brod

Datum	30/08/2023	Revize è.	1775716-1	07
Vyhotovil	M.Tokarz-Druzba	Výkres è.	1	1
Zkontroloval		Pøípustné zatížení v kg	indicated	
Mìøítko	1:75			

POTVRZENÍ ZÁKAZNÍKA: SYSTÉM A ROZMÌRY VE VÝKRESU

Tento dokument je majetkem spoleènosti MECALUX, S.A., jeho úplná èi èásteèná reprodukce nebo jeho pøedání tøetím osobám je zakázáno